#### **VARI\*LITE**

### VL5LED WASH



The Vari-Lite VL5LED WASH is a true modern update to the legendary VL5. This compact, high output LED wash fixture brings a host of modern features to the familiar form factor of this unique fixture. The Dichro\*fusion blades, first seen in the VL6500 WASH, supply smooth, variable diffusion while the RGBALC color system provides a wide range of rich color options. To simplify setup and programming of this color system, the innovative SmartColor Control System gives designers adjustability without complexity. The beautiful colors of the VL5LED are reflected on the Dichro\*fusion blades, which bring the vintage stylings of the original VL5 to create a strong visual element on stage. For further visual options, a separate ring of LEDs light up the Dichro\*fusion blades a different color than the light coming from source engine. The LED blade lights, along with an onboard motorized zoom, offers a range of new visual options and bring more flexibility to this classic fixture.



## VL5LED WASH

#### FEATURES AND BENEFITS

- Compact, high output LED wash fixture get a high-output, Vari-Lite quality wash out of a compact LED fixture.
- **High CRI RGBALC Color System with SmartColor Control -** wide range of vivid color options that are easy to program
- Classic VL5 form factor and Dichro\*fusion diffusion blades vintage styling reminiscent of the legendary VL5, offering a strong visual element on stage.
- **LED blade lights with built-in effects -** LEDs light up the blades a different color than the beam, with chases and other built-in effects. Add a new, easy-to-program creative element to this iconic fixture.
- Motorized zoom and variable diffusion beautiful wash options available for any application
- Quiet operation with Standard, Studio, and Whisper modes perfect for use in quiet environments

## VARI\*LITE

# VL5LED WASH

SOURCE					
	Туре	Osram RGBALC LED			
	Wattage	18 x 60W			
OPTICAL PERFORMANCE					
	Output lumens	13000			
	Output CRI	>90			
	Output CCT	Variable 2700-7000K			
		LUX	FOOT-CANDLES		
	Narrow @ 5m				
	Wide @ 5m				
	Narrow @ 10m				
	Wide @ 10m				
BEAM					
	Angle	10-40°			
SPECIAL EFFECTS					
	Visual effects	16 dedicated - Color mixing LED Blade lights, with macro effects and DMX controlled modifiers			
	Strobe effects	Main array	Regular, random, and random sync		
	Strobe effects	LED blade	Regular, random and random sync		
COLOR SYSTEM					
	Color mixing	RGBALC			
	сто	Dedicated black body curve channel (smart color mode)			
	Green shift	Dedicated green / magenta shift channel (smart color mode)			
	Color preset	Dedicated calibrated color presets			
MOVEMENT					
	Max pan angle 540° / 630°				
	Full pan speed	2.7s / 3s			
	Max tilt angle	226°			
Full tilt speed 1.4s					





## VL5LED WASH

NOISE LEVELS (BASE LEVEL 18.6db)					
F	ull operation				
S	Standby				
F	an modes	Standard, Studio, Whisper			
USER IN	TERFACE				
т	Гуре	6-button color screen with battery back up and auto flip			
POWER					
R	Range	120-240V at 50/60Hz			
C	Connection	Power in only			
C	Connector type	Neutrik TrueOne			
V	Wattage (max)	1320W			
DATA					
C	Control protocols	DMX / RDM, ArtNet, sACN			
_		XLR 5 in & Thru			
D	Data connections	RJ45 Ethercon			
_		USB (diagnostics - firmware)			
r	DMX modes	Smart Color control Mode - 29Channels (Default)			
	on a modes	Open Source color control - 33 channels			
PHYSICALS					
II.	P rating	20			
F	inish	Black			
DIMENSI	IONS (H x W x L)	mm	in		
F	ixture only	573 x 361 x 366	22.6 x 14 x 14.4		
	Packed dimensions				
	langing type	Vari-Lite mini rails			
	langing centers				
WEIGHT		kg	lb .		
_	ixture only	23.5	52		
	Packed weight				
WARRANTY & APPROBATIONS					
_	Warranty	2 years			
_	Approval / listings	CE, ETL, UL, FCC CSA, RoHS, ISO 9001			



## VL5LED WASH





PRODUCT NAME

VL5LED WASH

912400575018

©2019 Signify Holding. All rights reserved.

All trademarks are owned by Signify Holding or their respective owners. The information provided herein is subject to change, without notice. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Data subject to change.

Ref: 912400575018-100-v00